

Superior Comfort, Performance and Style



3-wheel version

4-wheel version



CELEBRITY DX

3 & 4-Wheel Scooters



Angle-adjustable tiller

The **Celebrity® DX** delivers superb performance and ease of use with sleek, sporty styling for an overall package that impresses with elegant simplicity. Loaded with standard features like a deluxe seat with headrest and manual recline, and lower light for pathway illumination, the Celebrity DX is equipped to excite.


PRIDE® **MOBILITY SCOOTERS**
LIVE YOUR BEST®

pridemobility.com.au



Specifications

3W: SC4001DXAUS 4W: SC4401DXAUS

Weight Capacity	159 kg (350 lbs.)
Maximum Speed ¹	Up to 9.65 km/h (6 mph)
Ground Clearance ²	8.26 cm (3.25")
Turning Radius ²	3W: 105.41 cm (41.5") 4W: 149.86 cm (59")
Overall Length ²	3W: 116.84 cm (46") 4W: 118.75 cm (46.75")
Overall Width ²	61 cm (24")
Front Tyres	9 cm x 25 cm (3.5" x 10")
Rear Tyres	10 cm x 25 cm (4" x 10")
Range Per Charge ^{2,4}	Up to 20.63 km (12.8 miles)
Total Weight Without Batteries	3W: 62.14 kg (137 lbs.) 4W: 65.31 kg (144 lbs.)
Heaviest Piece When Disassembled	3W: 25.40 kg (56 lbs.) front section 4W: 29.02 kg (64 lbs.) front section
Standard Seating	<i>Type: Deluxe seat with headrest and manual recline</i> <i>Material: Black Vinyl</i> <i>Dimensions: Width: 45.72 cm (18"), Depth: 45.72 cm (18")</i>
Motor Output	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12-volt, deep cycle Size: 32 AH or 40 AH Weight: 32 AH: 11.11 kg (24.5 lbs.) each 40 AH: 14.5 kg (32 lbs.) each
Battery Charger	5-amp, off-board
Colour	

Red

Features

- State-of-the-art rear suspension
- Ultra-simple, auto-latching lockup for quick disassembly and assembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket and rearview mirror standard
- Includes standard angle-adjustable light
- Front frame-mounted seat post for optimal stability
- High visibility reflectors
- Microprocessor-based controller
- Tiller rotation lock permits tiller to be used as a handle during transport
- Speed reduction technology automatically reduces travel speed while turning corners (4-wheel only)



Easy-drive tiller with wraparound handles



Shown disassembled

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 3 AGM or gel cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.